## **Project Completion Report for Grid-Connected Rooftop**

Financial year *:		
Approval No. *:		
Proposal Title :		
Installed by agency:		
Title of the Project*:	SPV Capacity	
	(kWp)*:	
Category of the	Name of the	
organization/	contact person*	
beneficiary*:	:	
Address of contact person*:	·	
State*:	District/City*:	
Mobile*:	Email*:	
Aadhaar Card Number (For	Latitude:	
Residential) Copy to be attached.		
	Longitude:	
Other info		
Electricity Distribution Company	Sanction Load	
Name:		
Electricity consumer account no. as		
per electricity bill:		
·		

Technology Description & System Design /Specification				
(Compliance to BIS/ IEC Standards is mandatory – Attach Copies)				
1. Solar PV Module:				
Power of each PV Module /				
Nos.(Wp)* / Make				
Cumulative Capacity of				
Modules(kWp):				
Solar cell technology:	Tilt Angle of			
	Modules:			
Module efficiency (in	Azimuth			
Percentage):				
Indigenous or imported	RFID passed			
	inside or outside:			
2. Inverters:				
Type of inverter:				

	Single Phase/ Three Phase	Type of Charge Controller / MPPT  Grid connectivity level Voltage  Surface Finish Wind Speed Tolerance  Length:	230 V/ 415 V
Capacity/Power of PCU/inverters (kVA):  Inverter efficiency (Full load): (in percentage)  Grid connectivity level phase  3. Mounting Structures  Type  Material	_	Controller / MPPT  Grid connectivity level Voltage  Surface Finish Wind Speed Tolerance	230 V/ 415 V
(kVA):  Inverter efficiency (Full load): (in percentage)  Grid connectivity level phase  3. Mounting Structures  Type  Material	_	Controller / MPPT  Grid connectivity level Voltage  Surface Finish Wind Speed Tolerance	230 V/ 415 V
Inverter efficiency (Full load): (in percentage) Grid connectivity level phase  3. Mounting Structures Type Material	_	Grid connectivity level Voltage  Surface Finish Wind Speed Tolerance	230 V/ 415 V
(in percentage) Grid connectivity level phase  3. Mounting Structures Type Material	_	level Voltage  Surface Finish  Wind Speed Tolerance	230 V/ 415 V
Grid connectivity level phase  3. Mounting Structures  Type  Material	_	level Voltage  Surface Finish  Wind Speed Tolerance	230 V/ 415 V
3. Mounting Structures  Type  Material	_	level Voltage  Surface Finish  Wind Speed Tolerance	230 V/ 415 V
3. Mounting Structures  Type  Material	Three Phase	Surface Finish Wind Speed Tolerance	
Type Material		Wind Speed Tolerance	
Material		Wind Speed Tolerance	
		Tolerance	
4 Cables:			
4 Cables		Length:	
Ti Cabica.		Length:	
DC Cable Make & Size			
AC Cable Make & Size		Length:	
(Inverter to ACDB)			
AC Cable Make & Size		Length:	
(ACDB to Electric Panel)			
Conductor	Multi strand	Insulation/sheath	PVC /XLPE
l	high		Insulated
	conductivity		
	Copper		
5. JUNCTION BOX & DISTRIBUTI	ION BOARDS		
Type	weatherproof,	Nos.:	
C	dust & vermin		
ŗ	proof		
Make			
6. EARTHING & LIGHTNING PRO	OTECTION		
EQUIPMENT EARTHING			
AC (Nos.)		Earth Resistance	
DC (Nos.)		Earth Resistance	
LIGHTNING ARRESTORS (LA)			
Type			
LA (Nos.)		Earth Resistance	

(Signature of Vendor) With Stamp